

MAXIMUS-3

JK/JL Tire Carrier Accessories

SIDE ROTOPAX MOUNT

SKU: UN2007SR

INSTALLATION GUIDES

PLEASE MAKE SURE YOU READ AND UNDERSTAND THE ENTIRE INSTALLATION GUIDE BEFORE YOU START. WE EXPECT YOU TO HAVE BASIC MECHANICAL ABILITIES TO PERFORM THIS INSTALLATION.

WE RECOMMEND THAT YOU SEPARATE AND IDENTIFY ALL THE PARTS AND HARDWARE KITS YOU RECEIVED WITH YOUR SHIPMENT BEFORE YOU PROCEED TO DISASSEMBLE YOUR VEHICLE.

Parts List:

	<u>Qty</u>
Maximus-3 Side Rotopax Mount	1
Rotopax	1
Anti-Vibration bump stops	2

Hardware Component List:

	<u>Qty</u>
M8 Truss Head Bolts – Stainless Steel	1
8 MM Flat Washers – Stainless Steel	1
Anti-vibration Bump Stop Bolts	2

Tools Required:

Basic wrench and Drive Sockets
Metric Allen key # 5



INSTALLATION STEPS

(A)- ASSEMBLE YOUR ROTOPAX MOUNT

1. Using the hardware pre-assemble the Rotopax Mount and T-handle to the Maximus-3 Rotopax Mount Bracket as shown below, left. Discard the round metal plate if your kit came with one.
2. Using the M8 Stainless Steel Bolts and Anti-Vibration bump stops supplied, bolt the Rotopax Mount assembly to the Carrier as shown below to the right.



Anti-Vibration Bump Stops

(B)- MOUNT YOUR ROTOPAXS

1. Mount your Rotopax following ROTOPAX's instructions provided.
2. Use a Rotopax 2-Gallon Mount Extension to carry 2 cans.



Use your Rotopax Cans according to manufacturer's instructions.

Your installation is complete. If you have questions regarding this installation, please contact us at info@maximus-3.com or call 248 821 6654.